



# elan 35 POWER

## Technical specifications

Length overall 11.01 m

Hull length 10.67 m

Beam overall 3.49 m

Dry weight 6400 kg

Fuel capacity 750 l

Fresh water capacity 200 l

Passengers 10

N° of berths 4 + 1

Project **Tony Castro**

Boat design category **B**

Declaration of conformity:

**Germanischer Lloyd**

Engine options:

**VOLVO PENTA**

**2 x D4-225 EVC/DP-H (2x225 HP)**

**VOLVO PENTA**

**2 x D4-260 EVC/DP-H (2x260 HP)**

January 2007

# elan 35

POWER

## STANDARD FEATURES EXTERIOR

### DECK

Foredeck locker - 700 W electric anchor winch - 13 kg Bruce anchor - 30 m/8 mm chain - Anchor stopper - Bow roller - Windlass handle - 2 bow, 2 spring and 2 stern stainless steel cleats - S. steel pulpit - 2 s. steel sun bed handrails - 4 deck hatches (3 opening) - 9 opening port lights - Radar arch - S. steel hardtop handrails - Open able sliding roof - Windscreen with glass front and sides (Hardtop) - Aluminium framed windshield with tinted glass (Open) - Windshield wiper with spray nozzle - 2 s. steel fuel filler caps (port/stbd) and water filler cap - Fuel tank air vents (2) with anti-flame and anti-spray net - Water tank vent - Open bow guardrail - S. steel rub rail - S. steel air intake lattice

### TRANSOM

Teak-laid swimming platform - Steps for access to side deck - Foldaway swimming ladder - Shower with mixer tap -32A/220V shore power socket with shore power cable - Ropes stowage - Trim tabs

### COCKPIT

Self-draining cockpit - Teak steps for access to side deck - GRP Roll-Bar - S. steel mast - Navigation lights - Horn - Cockpit bar with sink, mixer tap and Kerrock top surface - Ice bin - Pilot's and co-pilot's seat - 3 kg gas bottle compartment - Cockpit table - 6 s. steel cockpit handrails - 6 stowage lockers - Transom entrance door from stern platform - Fire extinguishers - Cups and other objects holder- Teak laid cockpit

## HELM POSITION

EVC engine controls - Power steering - Steering wheel - Complete engine instrumentation: oil pressure and water temperature gauges, voltmeters, hour-counter, revs. counter, power-trim control and indicators - Echo/Log/Speed (total and partial mileage recorder + echo sounder) - Rudder angle indicator - Fuel level gauge - Compass - Horn control - Navigation and mooring lights control - Anchor-winch control - Screen wiper control - Engine hatch control - Navigatorium with Plexiglas cover - Stainless steel handrail - Driver's foldable step

## INTERIOR

Note: Furniture is made out of cherry wood (high gloss finish)

## SALOON & GALLEY

Plexiglas sliding access door to cabin - Dinette seating convertible into bed - Adjustable cherry wood table - Bar unit - 220 Volt power sockets - Microwave oven - Switch panel - Water level gauge - Illumination - Galley unit with Kerrock top - Hob with two gas burners - S. steel sink with mixer tap - 65 l. refrigerator - Waste bin - Port light Venetian blinds - Drawers - Owner's manual - Cupboards and storage space for tableware in cherry wood

## MASTER CABIN

Owner's bed with chest of drawers - Wardrobe in cherry wood - Reading lights - Spotlights - 220 V power socket - Curtains

## AFT CABIN

Twin beds - Storage lockers - Divan - Wardrobes in cherry wood - Reading lights - Spotlights - 220 V power socket - Curtains

## TOILET

Electric marine WC with outlet safety valves - Sink with mixer tap/shower - Kerrock top surface - Mirror - Shower curtain - Teak grating - Cupboards in cherry wood - 220 Volt power socket - Automatic shower water discharge system - Spotlights - Shower curtain -

## ELECTRICAL SYSTEM

12 volt electrical system - 2 x135Ah service batteries; 1x150 Ah start battery - Electric panel, magneto-thermal protected - 32 Amp/220 Volt stern socket with cable - Automatic 50 Amp/h battery charger - 220 volt differential fuse - Power sockets - Automatic shore/generator switch on - Windlass protection magneto-thermal switch - Battery switches - Emergency battery coupling system - Galvanic isolator - Preparation for generator and bow thruster

## FUEL SYSTEM/BILGE PUMPS

S. steel 750 ltr. capacity fuel tank with manual inspection hatch and dipstick - Rubber fuel pipes with flexible heads - Additional fuel filters - Fuel cut-off valves - Bilge drainage by 2 electric 120 l/min bilge pumps with manual control and one manual bilge pump

## WATER SYSTEM

200 ltr. approx. capacity non-toxic food quality polyethylene water tank - Water pump - Hot water electric boiler 24 ltr. - Waste water tank 80 ltr.

**Elan Marine d.o.o.**

Begunje 1, SI-4275, Begunje na Gorenjskem, Slovenia

Phone: +386 4 535 13 70, Fax: +386 4 535 13 60

E-mail: [elan.marine@elan.si](mailto:elan.marine@elan.si)

[www.elan-yachts.com](http://www.elan-yachts.com)

